

ZEETEX



EFFICIENCY ENGINEERED
ZEETEX ECO SERIES

For Vans and Transport Vehicles

CT6000 eco



Rugged construction helps in withstanding challenging conditions in cargo transport.

Specially designed tread pattern with shoulder lugs provides better cornering, stability & resistance against off-road abuse.

Zig-zag circumferential grooves help in quicker water evacuation to overcome aquaplaning and providing extra-ordinary road grip in wet conditions.

Series	Size	PR	Load & Speed Index	Maximum Load (Single)	Maximum Load (Dual)	Max Inflation Pressure	Rim Width	Section Width	Overall Diameter	Tread Depth
				kgs	kgs	psi	inches	mm	mm	mm
75	185/75R16C	8	104/102T	900	850	69	5.0	184	684	8.0
	195/75R16C	8	107/105T	975	925	69	5.5	196	698	8.0
	205/75R16C	8	110/108T	1060	1000	69	5.5	203	714	8.0
	215/75R16C	8	113/111T	1150	1090	69	6.0	216	728	8.0
70	175/70R14C	8	95/93T	690	650	54	5.0	177	602	8.0
	195/70R15C	8	104/102T	900	850	65	6.0	201	655	8.0
	205/70R15C*		106/104T	950	900	65	6.0	209	644	8.0
	215/70R15C	8	109/107T	1030	975	65	6.5	221	683	8.0
	225/70R15C	8	112/110T	1120	1060	65	6.5	228	697	8.0
65	205/65R15C	6	102/100T	850	800	54	6.0	209	647	8.0
	215/65R15C*	8	104/102T	900	850	54	6.5	221	661	8.0
	195/65R16C	8	104/102T	900	850	69	6.0	201	660	8.0
	205/65R16C	8	107/105T	975	925	69	6.0	209	672	8.0
	215/65R16C	8	109/107T	1030	975	69	6.5	221	686	8.0
	225/65R16C	8	112/110T	1120	1060	69	6.5	228	698	8.0
	235/65R16C	8	115/113T	1215	1150	69	7.0	240	712	8.0
60	215/60R16C*	8	103/101T	1000	950	69	6.5	221	664	8.0
	215/60R17C*	8	109/107T	1030	975	69	6.5	221	690	8.0
LTRC	185R14C	8	102/100T	850	800	65	5.5	189	652	8.0
	195R14C	8	106/104T	950	900	65	5.5	196	668	8.0

* Newly added sizes

Pattern availability may slightly vary based on country, please reach out to your account manager for details.

For Vans and Transport Vehicles

CT6001 eco



Wider tread design for excellent riding stability, which ensures safety and high mileage.

Optimal footprint due to wider shoulders' profile for enhanced stability.

Heavy duty casing construction that can withstand overload; stone ejectors to prevent casing damage.

Series	Size	PR	Load & Speed Index	Maximum Load (Single)	Maximum Load (Dual)	Max Inflation Pressure	Rim Width	Section Width	Overall Diameter	Tread Depth
				kgs	kgs	psi	inches	mm	mm	mm
LTRC	195R15C	8	106/104R	920	875	65	5.5	196	693	9.0

Pattern availability may slightly vary based on country, please reach out to your account manager for details.

For High-performance and Luxury Vehicles

HP6000 eco



Serrations on the groove wall reduce pipe resonance, delivering an exceptionally silent ride.

Absorption of road inputs delivers extra-ordinary driving comfort.

Improved vehicle stability & reduced braking distance in wet & dry conditions.

Series	Size	Load & Speed Index	Maximum Load	Max Inflation Pressure	Rim Width	Section Width	Overall Diameter	Tread Depth
			kgs	psi	inches	mm	mm	mm
65	205/65R16*	95H	690	44	6.0	209	672	8.2
60	215/60R17	96H	710	44	6.5	221	690	8.2
	225/60R17	99H	775	44	6.5	228	702	8.2
	235/60R18	103H	875	44	7.0	240	739	8.2
55	205/55ZR16	91W	600	44	6.5	214	632	7.6
	215/55R16	97V XL	725	49	7.0	226	642	7.6
	225/55ZR16	95W	775	51	7.0	266	654	7.6
	205/55ZR17	95W XL	690	49	6.5	214	658	7.6
	215/55ZR17	98W XL	750	51	7.0	226	668	7.6
	225/55ZR17	101W XL	825	51	7.0	233	680	7.6
	235/55ZR17	103W XL	775	44	7.5	245	690	7.6
	215/55ZR18	99W XL	775	49	7.0	226	693	7.6
	225/55R18	98V	750	44	7.0	233	705	7.6
	235/55ZR18	104W XL	900	49	7.5	245	715	7.6
	235/55ZR19	101W	825	44	7.5	245	741	7.6
	245/55ZR19*	103W	875	44	7.5	253	753	7.6
	235/55ZR20*	105W XL	925	49	7.5	245	766	7.6
50	195/50R16	88V XL	500	44	6.0	201	602	7.6
	205/50ZR16	91W XL	545	44	6.5	214	612	7.6
	205/50ZR17	93W XL	650	49	6.5	214	638	7.6

* Newly added sizes

Pattern availability may slightly vary based on country, please reach out to your account manager for details.

Series	Size	Load & Speed Index	Maximum Load	Max Inflation Pressure	Rim Width	Section Width	Overall Diameter	Tread Depth
			kgs	psi	inches	mm	mm	mm
50	215/50ZR17	95W XL	615	44	7.0	226	648	7.6
	225/50ZR17	98W XL	750	51	7.0	233	658	7.6
	235/50ZR18	101W XL	825	51	7.5	245	693	7.6
	245/50R18*	104W XL	900	49	7.5	253	703	7.6
	255/50ZR19	107W XL	975	49	8.0	265	739	7.6
	265/50R19*	110W XL	1060	49	8.5	277	749	7.6
	245/50ZR20*	102W	925	49	7.5	253	754	7.6
	275/50R20*	113W XL	1150	49	8.5	284	784	7.6
45	205/45ZR16	87W XL	545	49	7.0	206	590	7.6
	205/45ZR17	88W XL	560	49	7.0	206	616	7.6
	215/45ZR17	91W XL	615	51	7.0	213	626	7.6
	225/45ZR17	94Y XL	670	49	7.5	225	634	7.6
	235/45ZR17	97W XL	730	51	8.0	236	644	7.6
	245/45ZR17	99W XL	775	51	8.0	243	652	7.6
	215/45ZR18	93W XL	650	49	7.0	213	651	7.6
	225/45ZR18	95Y XL	690	49	7.5	225	659	7.6
	235/45ZR18	98W XL	750	49	8.0	236	669	7.6
	245/45ZR18	100Y XL	800	51	8.0	243	677	7.6
	225/45ZR19*	92W	630	44	7.5	225	685	7.6
	245/45ZR19	102W XL	850	49	8.0	243	703	7.6
	245/45ZR20	103W XL	875	49	8.0	243	728	7.6
	275/45ZR21	110W XL	1060	49	9.0	273	781	7.6
40	205/40ZR17	84W XL	500	51	7.5	212	596	7.6
	225/40ZR18	92Y XL	630	51	8.0	230	637	7.6
	235/40ZR18	95Y XL	690	51	8.5	241	645	7.6
	245/40ZR18	97Y XL	730	51	8.5	248	653	7.6
	255/40ZR18	99W XL	775	49	9.0	260	661	7.6
	225/40ZR19	93W XL	650	49	8.0	230	663	7.6
	235/40ZR19	96W XL	710	49	8.5	241	671	7.6
	245/40ZR19	98W XL	750	49	8.5	248	679	7.6
	255/40ZR19	100Y XL	800	49	9.0	260	687	7.6
	275/40ZR19	105W XL	925	49	9.5	278	703	7.6
	275/40ZR20*	106W XL	950	51	9.5	278	728	7.6
	295/40ZR21*	111W XL	1090	49	10.5	301	769	7.6
35	215/35ZR18*	84W XL	500	49	7.5	218	607	7.6
	265/35ZR18	97W XL	730	49	9.5	271	643	7.6
	235/35ZR19	91W XL	615	49	8.5	241	647	7.6
	245/35ZR19	93W XL	650	49	8.5	248	655	7.6
	255/35ZR19*	96W XL	710	49	9.0	260	661	7.6
	275/35ZR19	100W XL	800	49	9.5	278	675	7.6
30	275/30ZR20	97W XL	730	49	9.5	278	674	7.6

* Newly added sizes

Pattern availability may slightly vary based on country, please reach out to your account manager for details.

For 4x4's on Highway Terrain

HT6000 eco



Symmetrical tread design with large shoulders blocks for optimized footprint and increased stability.

Four zigzag grooves offers enhanced handling and drive comfort.

Multi-type sipes for optimal grip on different highway roads conditions.

Series	Size	Load & Speed Index	Maximum Load	Max Inflation Pressure	Rim Width	Section Width	Overall Diameter	Tread Depth
			kgs	psi	inches	mm	mm	mm
70	245/70R17	108H	1000	44	7.0	248	776	9.0
	265/70R17	113H	1150	44	8.0	272	804	9.0
65	225/65R17	102H	850	44	6.5	228	724	9.0
	245/65R17	105H	925	44	7.0	248	750	9.0
	265/65R17	110H	1060	44	8.0	272	776	9.0
	285/65R17	115H	1215	44	8.5	292	802	9.0
	275/65R18	114H	1180	44	8.0	279	815	9.0
55	275/55R20	117H XL	1285	49	8.5	284	810	9.0

Pattern availability may slightly vary based on country, please reach out to your account manager for details.

For 4x4's on Highway Terrain

HT6001 eco



Optimized tread pattern provide great ride comfort, lower noise levels & handling on the road.

Solid center rib with optimal provide steering stability performance at high speed

Wide open tread channels to evacuate water rapidly for better road grip.

								P Metric
Series	Size	Load & Speed Index	Maximum Load	Max Inflation Pressure	Rim Width	Section Width	Overall Diameter	Tread Depth
			kgs	psi	inches	mm	mm	mm
75	235/75R15	108T XL	990	49	6.5	235	733	10.5
70	225/70R16	103T	825	44	6.5	228	722	10.5
	245/70R16	111T XL	1090	49	7.0	248	750	10.5
	255/70R16	109T	1030	44	7.5	260	764	10.5

										LT Metric
Series	Size	PR	Load & Speed Index	Maximum Load (Single)	Maximum Load (Dual)	Max Inflation Pressure	Rim Width	Section Width	Overall Diameter	Tread Depth
				kgs	kgs	psi	inches	mm	mm	mm
75	LT 265/75R16*	10	123/120Q	1550	1400	80	7.5	267	804	12.0
	LT 285/75R16*	10	126/123Q	1700	1550	80	8.0	286	834	12.0
70	LT 245/70R17*	10	119/116Q	1360	1250	80	7.0	248	776	12.0

* Newly added sizes

Pattern availability may slightly vary based on country, please reach out to your account manager for details.

For 4x4's on Mud Terrain

MT6000 eco



Aggressive tread blocks maintain great off-road traction & grip on mud and loose soil.

Reinforced top sidewall with increased rubber thickness for optimal protection against critical sidewall failure zone and to improve the tear resistance.

Cut & chip resistance tread rubber compound withstands off-road abuse while driving on extremely tough road conditions & mud terrains

Series	Size	PR	Load & Speed Index	Maximum Load (Single)	Maximum Load (Dual)	Max Inflation Pressure	Rim Width	Section Width	Overall Diameter	Tread Depth
				kgs	kgs	psi	inches	mm	mm	mm
75	LT 265/75R16	10	123/120Q	1550	1400	80	7.5	267	804	16.5
	LT 285/75R16	10	126/123Q	1700	1550	80	8.0	286	834	16.5
70	LT 265/70R17	10	121/118Q	1450	1320	80	8.0	272	778	16.5
	LT 285/70R17	10	121/118Q	1450	1320	80	8.5	292	832	16.5
Flotation	LT 33X12.50R17	8	114Q	1180	-	51	10.0	318	826	16.5
	LT 35X12.50R17	10	121Q	1450	-	65	10.0	318	877	16.5
	LT 35X12.50R18	10	123Q	1550	-	65	10.0	318	877	16.5

Pattern availability may slightly vary based on country, please reach out to your account manager for details.

For Crossovers and Sports Utility Vehicles

SU6000 eco



Optimized construction & tread design ensure wider footprint thereby having unparalleled road contact providing overall driving safety and stability.

Specially engineered sipes on the inner ribs reduce rolling resistance.

Shoulder and inner ribs with wider grooves retain excellent dry and wet braking performance and very good handling properties

Series	Size	Load & Speed Index	Maximum Load	Max Inflation Pressure	Rim Width	Section Width	Overall Diameter	Tread Depth
			kgs	psi	inches	mm	mm	mm
60	245/60R18*	105V	925	44	7.0	248	751	8.0
	285/60R18*	120V XL	1400	49	8.5	292	799	8.0
	275/60ZR20*	116V XL	1360	49	8.0	279	838	7.2
55	255/55ZR18	109W XL	1030	49	8.0	265	737	8.0
	225/55ZR19*	99W	775	44	7.0	265	763	7.4
	255/55ZR19*	107W	975	44	8.0	265	712	7.2
	275/55ZR20*	117W XL	1285	49	8.5	284	810	7.2
50	235/50ZR17*	100W XL	800	49	7.5	245	668	7.2
	225/50ZR18*	99W XL	775	49	7.0	233	683	7.2
	265/50ZR20	111W XL	1090	49	8.5	277	774	8.0
	285/50R20*	116W XL	1250	49	9.0	297	794	8.0
	275/50ZR21*	113W XL	1150	49	8.5	284	809	7.2
45	195/45R16*	84V XL	500	49	6.5	195	582	7.2
	215/45ZR16*	90W XL	600	49	7.0	213	600	7.2
	255/45ZR18*	103W XL	875	49	8.5	255	687	7.4
	235/45ZR19*	99W XL	775	49	8.0	243	703	7.2
	265/45ZR20*	108Y XL	1000	49	9.0	266	746	7.2
	275/45ZR20	110W XL	1060	49	9.0	273	756	8.0
	285/45ZR22*	114W XL	1180	49	9.5	285	815	7.2

* Newly added sizes

Pattern availability may slightly vary based on country, please reach out to your account manager for details.

Series	Size	Load & Speed Index	Maximum Load	Max Inflation Pressure	Rim Width	Section Width	Overall Diameter	Tread Depth
			kgs	psi	inches	mm	mm	mm
40	215/40ZR17*	87W XL	545	49	7.5	218	604	7.2
	245/40ZR17*	95W XL	690	49	8.5	248	628	7.2
	205/40ZR18*	86W XL	530	49	7.5	212	621	7.2
	215/40ZR18*	89W XL	580	49	7.5	218	629	7.2
	245/40ZR20	99W XL	775	49	8.5	248	704	7.2
	255/40ZR20*	101W XL	825	49	9.0	260	712	7.2
	265/40ZR20	104W XL	900	49	9.5	271	720	8.0
	275/40ZR20	106W XL	950	49	9.5	278	728	8.0
	265/40ZR21	105W XL	925	49	9.5	271	745	8.0
	265/40ZR22*	106W XL	950	49	9.5	271	771	7.2
	275/40ZR22*	107W XL	975	49	9.5	278	779	7.2
	285/40ZR22*	110W XL	1060	49	10.0	290	787	7.2
	305/40ZR22*	114W XL	1180	49	11.0	313	803	8.0
35	255/35ZR18*	94Y XL	670	49	9.0	260	635	7.2
	275/35ZR18*	99Y XL	775	49	9.5	278	649	7.2
	215/35ZR19*	85W XL	515	49	7.5	218	633	7.2
	225/35ZR19*	88Y XL	515	49	8.0	230	641	7.2
	255/35ZR19*	96W XL	710	49	9.0	260	661	7.4
	235/35ZR20*	92Y XL	630	49	8.5	241	672	7.2
	255/35ZR20*	97Y XL	730	49	9.0	260	686	7.2
	275/35ZR20*	102Y	850	49	9.5	278	700	7.2
	315/35ZR20*	110Y XL	1060	49	11.0	320	728	7.2
	295/35ZR21*	107W XL	975	49	10.5	301	739	7.2
	265/35ZR22*	102W XL	850	49	9.5	271	745	7.2
	285/35ZR22	106W XL	950	49	10.0	290	759	8.0
30	265/30ZR19*	93Y XL	650	49	9.5	271	643	7.2

* Newly added sizes

Pattern availability may slightly vary based on country, please reach out to your account manager for details.

For Crossovers and Sports Utility Vehicles

SU6001 eco



Optimized symmetrical tread design ensure wider footprint thereby having unmatched road contact providing overall driving safety and stability.

Rigid centre tread blocks provide precise steering fastness in the longitudinal drive.

Multi typed sipes increase grip on wet and dry roads.

Series	Size	Load & Speed Index	Maximum Load	Max Inflation Pressure	Rim Width	Section Width	Overall Diameter	Tread Depth
			kgs	psi	inches	mm	mm	mm
75	235/75R15	105H	925	44	6.5	235	733	8.5
70	215/70R16*	100H	800	44	6.5	221	708	8.5
	225/70R16	103T	875	44	6.5	228	722	8.5
	235/70R16	106T	950	44	7.0	240	736	8.5
	245/70R16	111H XL	1090	49	7.0	248	750	8.8
	255/70R16	111H	1090	44	7.5	260	764	8.8
	265/70R16	112H	1120	44	8.0	272	778	8.8
65	215/65R17*	99H	775	44	6.5	221	712	8.5
	225/65R17	102H	850	44	6.5	228	724	8.5
	235/65R17	108H XL	1000	49	7.0	240	738	8.5
	245/65R17	111H XL	1090	49	7.0	248	750	8.8
	265/65R17*	112H	1120	44	8.0	272	776	8.8
	235/65R18	106H	950	44	7.0	240	763	8.5
60	235/60R17*	106H XL	950	49	7.0	240	714	8.5
	225/60R18	100H	800	44	6.5	228	727	8.5
	265/60R18	114H	1180	49	8.0	272	775	8.5

* Newly added sizes

Pattern availability may slightly vary based on country, please reach out to your account manager for details.

For Passenger Cars

ZT6000 eco



Symmetric tread design ensures smoother rolling on the road and even treadwear throughout the tire's life.

Wider grooves help in quicker dissipation of water thereby enhancing braking & stability on wet conditions.

Three inner ribs & optimal pitch variation reduces road noise and improves ride comfort.

Series	Size	Load & Speed Index	Maximum Load	Max Inflation Pressure	Rim Width	Section Width	Overall Diameter	Tread Depth
			kgs	psi	inches	mm	mm	mm
80	145/80R13*	75T	387	44	4.0	145	562	6.5
70	155/70R13	75T	387	44	4.5	157	548	7.0
	165/70R13	79T	437	44	5.0	170	562	7.0
	175/70R13	82T	475	44	5.0	177	576	7.0
	165/70R14	81T	462	44	5.0	170	588	7.0
	175/70R14	84T	500	44	5.0	177	602	7.0
	185/70R14	88T	560	44	5.5	189	616	7.0
	195/70R14*	91T	615	44	6.0	201	630	7.0
	205/70R15*	96H	710	44	6.0	209	669	7.0
65	155/65R13*	73T	365	44	4.5	157	532	7.0
	165/65R13*	77T	387	44	5.0	170	544	7.0
	155/65R14*	75T	387	44	4.5	157	558	7.0
	165/65R14	79T	437	44	5.0	170	570	7.0
	175/65R14	82T	475	44	5.0	177	584	7.0
	185/65R14	86H	530	44	5.5	189	596	7.0
	175/65R15	84H	500	44	5.0	177	609	7.0
	185/65R15	88H	560	44	5.5	189	621	7.0
	195/65R15	91V	615	44	6.0	201	635	7.0
	205/65R15	94H	670	44	6.0	209	647	7.0
	205/65R16*	95H	690	44	6.0	209	672	7.0
	215/65R16	98H	750	44	6.5	221	686	7.0

* Newly added sizes

Pattern availability may slightly vary based on country, please reach out to your account manager for details.

Series	Size	Load & Speed Index	Maximum Load	Max Inflation Pressure	Rim Width	Section Width	Overall Diameter	Tread Depth
			kgs	psi	inches	mm	mm	mm
60	165/60R14	75H	387	44	5.0	170	554	7.0
	185/60R14	82H	475	44	5.5	189	578	7.0
	165/60R15*	81H XL	462	49	5.0	170	579	7.0
	175/60R15*	81V	462	44	5.0	177	591	7.0
	185/60R15	84H	500	44	5.5	189	603	7.0
	195/60R15	88H	560	44	6.0	201	615	7.0
	205/60R15	91V	615	44	6.0	209	627	7.0
	195/60R16*	89H	580	44	6.0	201	640	7.0
	205/60R16	92V	630	44	6.0	209	652	7.0
	215/60R16	95V	690	44	6.0	221	664	7.0
55	165/55R14*	72H	355	44	5.0	170	538	7.0
	185/55R14*	80H	450	44	6.0	194	560	7.0
	165/55R15*	75H	387	44	5.0	170	563	7.0
	185/55R15	82V	475	44	6.0	194	585	7.0
	195/55R15	85V	515	44	6.0	201	595	7.0
	205/55R15*	88V	560	44	6.5	214	607	7.0
	185/55R16*	83V	487	44	6.0	194	610	7.0
	195/55R16	87V	545	44	6.0	201	620	7.0
	205/55R16	91V	615	44	6.5	214	632	7.0
50	165/50R15*	72V	355	44	5.0	170	547	7.0
	195/50R15	82V	475	44	6.0	201	577	7.0

* Newly added sizes

Pattern availability may slightly vary based on country, please reach out to your account manager for details.

For Passenger Cars

ZT6001 eco



Optimized center ribs ensure precise steering, increase road grip and traction.

Large shoulder blocks ensure better cornering & stability.

Four main wide grooves to retain excellent dry and wet braking performance

Series	Size	Load & Speed Index	Maximum Load	Max Inflation Pressure	Rim Width	Section Width	Overall Diameter	Tread Depth
			kgs	psi	inches	mm	mm	mm
80	155/80R13*	79T	437	44	4.5	157	578	8.0
70	185/70R13	86T	530	44	5.5	189	590	7.0
	205/70R14	98H XL	750	49	6.0	209	644	7.0
65	155/65R13	73T	365	44	4.5	157	532	8.0
	165/65R13	77T	412	44	5.0	170	544	7.0
	175/65R13	80T	450	44	5.0	177	558	8.0
60	175/60R13	77T	412	44	5.0	177	576	8.0
	195/60R14	86H	530	44	6.0	201	590	7.0

* Newly added sizes

Pattern availability may slightly vary based on country, please reach out to your account manager for details.



ZEETEX

Zeetex/Eco Series/August/2026

mea.zeetex.com



Zeetex MEA



@zeetexmea



Zeetex MEA